Product datasheet Isotape® 4560PV3 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



Isotap	e [®]	45	60	PV3
ISULAN	_	+3	vv	$\Gamma V J$

Isotape® 4560PV3 consists of acetate cloth with rubber adhesive.

Delivery forms

- Width: from 2.5 mm in 0.1 mm increments
- Core diameter: 76 mm (3")
- Special widths on request

Color					
White, black					
Glue					
Rubber					
Adhesive					
One-sided					

Storage

Updated 07/20

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.







SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		Isotape® 4560PV3
Standard colours		White, black
Backing		Acetate cloth
Backing thickness	mm	0.190
Adhesive		Rubber
Total thickness	mm	0.240
Elongation at break	%	16
Dielectic strength	kV	2.5
Tensile strength	N/cm	63
Adhesiveness / Adhesion to steel	N/cm	2.6
Thermal class		130 °C (B)







