Product datasheet SynTape® B 113/ P.34 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



# **SynTape**<sup>®</sup> **B 113/ P.34**

SynTape® B 113/ P.34 is a polyester adhesive tape with acrylate adhesive.

#### **Attributes**

The polyester adhesive tape P.34 has good resistance to impregnants and can be universally used for insulating purposes. It is available as a yellow, green, red, blue, black and transparent tape.

### **Application**

Especially for core and interlayer insulation as well as final insulation of small transformers, taping and insulation of coils and wires. It has good ageing resistance and is UL approved.

## **Delivery forms**

• Width: From 2.5 mm, in 0.1 mm increments

Standard length: 66 m
Core diameter: 76 mm (3")
Special widths on request

Glue		
<b>Glue</b> Acrylate		
Adhesive		
<b>Adhesive</b> one-sided		

## **Storage**

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.







SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	B113/P.34 coloured	B 113/P.34 transparent
Electrolyt. corrosion value		1	1
Thermal class		130 ° C/ B	130°C/ B
Dielectic strength	kV	4.5	4.5
Adhesiveness / Adhesion to steel	N/cm	2.5	3.5
Elongation at break	%	80	80
Tensile strength	N/cm	40	40
Total thickness	mm	0.060	0.060
Adhesive		Acrylate	Acrylate
Backing thickness	mm	0.023	0.023
Backing		Polyester film	Polyester
Standard colours		yellow, green, red, blue, black	transparent
Type/ Ordering information		B 113/ P.34	B 113/P.34





