

---

## SynTape® F 118/ H.20AC

SynTape® F 118/ H.20AC is a Kapton adhesive tape with acrylate adhesive for the highest electrical and chemical demands, and thermal demands in particular.

---

### Application

Insulation tape for the highest demands.

---

### Delivery forms

- Width: From 2.5 mm, in 0.1 mm increments
- Standard length: 66 m
- Core diameter: 76 mm (3")
- Special widths on request

---

### Glue

Acrylate

---

### Adhesive

one-sided

---

### Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

General	Unit of measure	
Type/ Ordering information		F 118/ H.20AC
Standard colours		brown
Backing		Kapton®
Backing thickness	mm	0.025
Adhesive		Acrylate
Thermal class		155 °C/ F
Electrolyt. corrosion value		1
Adhesiveness / Adhesion to steel	N/cm	4.0
Dielectric strength	kV	6
Elongation at break	%	35
Tensile strength	N/cm	45
Total thickness	mm	0.060

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 01/17

