

---

## Isotape® 6215PV3

Isotape® 6215PV3 is a polyester film tape with silicone adhesive.

---

### Delivery forms

- Width: from 2.5 mm in 0.1 mm increments
- Core diameter: 76 mm (3")
- Special widths on request

---

### Color

Green translucent

---

### Glue

Silicone

---

### Adhesive

One-sided

---

### Storage

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 12 months.

General	Unit of measure	
Type/ Ordering information		Isotape® 6215PV3
Standard colours		Green translucent
Backing		Polyester film
Backing thickness	mm	0.050
Adhesive		Silicone
Total thickness	mm	0.089
Dielectric strength	kV	6
Elongation at break	%	110
Tensile strength	N/cm	78
Adhesiveness / Adhesion to steel	N/cm	3.5
Thermal class		130 °C (B)

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 07/20

Isotape® is a registered trademark of SynFlex.

