SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



Glass-fibre-duct-spacing-mats

Glass-fibre-profiles connected with insulating tapes.

Attributes

Glass-fibre-duct-spacing-mats are a cost effective cooling channel solutions with free selectable / adjustable distances of single profiles. Also different profile-shapes can be used in one mat.

Application

Glass-fibre-duct-spacing-mats are used in transformer and coils with cooling channels. They can be used in automated winding processes.

Standards

Insulating material class H (180 °C)

Delivery forms

Length: Up to 25 m Width: Up to 3000 mm Also deliverable in kits.

Base

Profiles:

- dogbone
- square
- round

Insulating tapes:

- SynTherm® YT510
- NOMEX®
- SynTherm® DMD
- SynTherm® APA
- SynTherm® NPN
- MYLAR® A

Other materials on request.







SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Casting resin		Polyester / Epoxy
Reinforcement		Glas-Roving
Fibre content	%	> 60
Specific weight	g/cm³	> 1.85
Bending strength	N/mm²	480
Bending strength E-Module	N/mm²	35x10^3
Tensile strength	N/mm²	450
Compressive strength	N/mm²	240
Dielectric constant		apprx. 4
Specific resistance	Ωxcm	10^12
1-Minvoltage test	kV/mm	8
Coefficient of expansion	K-1	10-15^-6
Water absorption	%	< 5
Thermal conductivity	W/m*K	0.3
Thermal class		H (180 °C)







