Product datasheet Isotape® 4238PV3 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



Isotape® 4238PV3			
Isotape® 4238PV3 is a glass fiber reinforced polyester tape with acrylate adhesive.			
Standards			
UL-File-No.: E315249			
Delivery forms			
Width: from 2.5 mm in 0.1 mm increments			
• Core diameter: 76 mm (3")			
Special widths on request			
Color			
Translucent			
Glue			
Acrylate			
Adhesive			
One-sided			

Storage

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 $^{\circ}$ C and 50 - 60 $^{\circ}$ C relative humidity. The storage period should not exceed 12 months.







SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		Isotape® 4238PV3
Standard colours		Translucent
Backing		Glass fiber reinforced polyester
Backing thickness	mm	0.130
Adhesive		Acrylate
Total thickness	mm	0.180
Elongation at break	%	10
Thermal class		155 °C (F)
Dielectic strength	kV	6.0
Tensile strength	N/cm	392
Adhesiveness / Adhesion to steel	N/cm	4.68







