

---

## Isotape® 4238PV3

Isotape® 4238PV3 is a glass fiber reinforced polyester tape with acrylate adhesive.

---

## Standards

UL-File-No.: E315249

---

## Delivery forms

- Width: from 2.5 mm in 0.1 mm increments
- Core diameter: 76 mm (3")
- Special widths on request

---

## Color

Translucent

---

## Glue

Acrylate

---

## Adhesive

One-sided

---

## Storage

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 12 months.

General	Unit of measure	
Type/ Ordering information		Isotape® 4238PV3
Standard colours		Translucent
Backing		Glass fiber reinforced polyester
Backing thickness	mm	0.120
Adhesive		Acrylate
Total thickness	mm	0.190
Elongation at break	%	14
Thermal class		155 °C (F)
Dielectric strength	kV	6.5
Tensile strength	N/cm	470
Adhesiveness / Adhesion to steel	N/cm	4.7

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 07/20

