Product datasheet Isotape® 4560PV3 Page 1

SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



Isotape [®] 4560PV3
Isotape® 4560PV3 consists of acetate cloth with rubber adhesive.
Delivery forms
Width: from 2.5 mm in 0.1 mm increments
• Core diameter: 76 mm (3")
Special widths on request

Color		
White, black		
Glue		
Rubber		
Adhesive		
One-sided		

Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.







SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		Isotape® 4560PV3
Standard colours		White, black
Backing		Acetate cloth
Backing thickness	mm	0.190
Adhesive		Rubber
Total thickness	mm	0.240
Elongation at break	%	16
Dielectic strength	kV	2.5
Tensile strength	N/cm	63
Adhesiveness / Adhesion to steel	N/cm	2.6
Thermal class		130 °C (B)





