Product datasheet Isotape® 54965PV3 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



Isotape® 54965PV3

Isotape[®] 54965PV3 is a PET film double-sided tape with acrylate adhesive with a red polypropylene liner.

Delivery forms

- Width: from 2.5 mm in 0.1 mm increments
- Core diameter: 76 mm (3")
- Special widths on request

Color			
Transparent			
Glue			
Acrylate			
Adhesive			
Double-sided			

Storage

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 12 months.





Product datasheet Isotape® 54965PV3 Page 2 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		Isotape® 54965PV3
Standard colours		Transparent
Backing		Polyester film
Backing thickness	mm	0.012
Adhesive		Acrylate
Total thickness	mm	0.210
Tensile strength	N/cm	21.6
Adhesiveness / Adhesion to steel	N/cm	10.1
Elongation at break	%	105





