
SYNTAPE B564

Due to its application as strips, SYNTAPE B564 can be optimally processed and offers high dielectric strength as well as a reinforced winding after impregnation, resulting in enhanced heat conduction and end product quality.

Attributes

SYNTAPE B564 is a polyester non-woven adhesive tape with synthetic rubber adhesive and is applied in the form of strips which make it permeable to impregnants. It can be applied according to the impregnant being used.

Application

As winding head insulation and phase separation. SYNTAPE® B564 is additionally used for masking cantilever coils and as stress relief for supply lines.

Standards

RoHS compliant according to 2011/65 EC.

UL file no. E301705

Delivery forms

Width: From 2.5 mm, in 0.1 mm increments

Standard length: 50 m

Core diameter: 76 mm (3")

Special widths: Available on request

Glue

Rubber

Adhesive

one-sided

Storage

Adhesive tapes should be stored in a cool, dry place at approx. 20°C and 50 - 60% relative humidity. The storage period should not exceed 6 months.



The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.
Updated 05/18

