

---

## SynTape® B 108/ P.315

SynTape® B 108/ P.315 is a polyester adhesive tape with good adhesiveness due to the thermosetting rubber adhesive.

---

### Attributes

The adhesive tape B 108/ P.315 has high initial adhesiveness and good mechanical load capacity.

---

### Application

As core and interlayer insulation, final insulation, taping and insulation of transformers, coils and wires, UL approved.

---

### Delivery forms

- Width: From 2.5 mm, in 0.1 mm increments
- Standard length: 66 m
- Core diameter: 76 mm (3")
- Special widths on request

---

### Glue

rubber

---

### Adhesive

one-sided

---

### Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

General	Unit of measure	
Type/ Ordering information		B 108/ P.315
Standard colours		yellow or black
Backing		Polyester film
Backing thickness	mm	0.050
Adhesive		Rubber
Thermal class		130 °C (B)
Electrolyt. corrosion value		1
Dielectric strength	kV	7
Adhesiveness / Adhesion to steel	N/cm	6
Elongation at break	%	100
Tensile strength	N/cm	70
Total thickness	mm	0.087