
SynTape® F/ PT.20-20

SynTape® F/ PT.20-20 is a polyester, non-woven stabilised polyester adhesive tape. It is suitable for all insulations and fixings; particularly cost-effective for this insulation class.

Attributes

The polyester adhesive tape SynTape® F/ PT.20-20 is characterised by its high electric strength. It is very easy to form.

Application

Suitable for all insulations and fixings; particularly cost-effective for this insulation class.

Delivery forms

- Width: From 2.5 mm, in 0.1 mm increments
- Standard length: 50 m
- Core diameter: 76 mm (3")
- Special widths on request

Glue

Acrylate

Adhesive

one-sided

Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

General	Unit of measure	
Type/ Ordering information		F/ PT.20-20
Standard colours		translucent
Backing		Polyester/ Polyester non-woven
Backing thickness	mm	0.098
Adhesive		Acrylate
Total thickness	mm	0.160
Tensile strength	N/cm	30
Elongation at break	%	45
Adhesiveness / Adhesion to steel	N/cm	8.0
Dielectric strength	kV	4.8
Thermal class		155 ° C/ F
Electrolyt. corrosion value		1