
SynTape® TRB16 Eco

SynTape® TRB16 Eco is a transparent pad-cleaning tape based on one-sided stamped polypropylene-film with excellent flatness.

Attributes

Our pad-cleaning tapes combine the actually opositional properties of safe removal from tint and dirt with avoiding adhesion transfer.

SynTape® TRB16 Eco is also excellent for machine processing.

Application

Cleaning of pad printheads

Delivery forms

- Core diameter 76 mm \pm 3 % (further diameters on request)
- Slotted cores are possible
- Standard length: 40 m and 50 m (further lengths on request)
- Special widths on request

Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

| General | Unit of measure | |
|----------------------------------|-----------------|--------------------|
| Type/ Ordering information | | SynTape® TRB16 Eco |
| Standard colours | | transparent |
| Backing (Laminate) | | polypropylene |
| Backing thickness | mm | 0.090 ± 10 % |
| Adhesiveness / Adhesion to steel | N/cm | 1.2 |
| Adhesive | | acrylate |

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 01/19

