
SynTape® TRB19 Optimo

SynTape® TRB19 Optimo is a transparent pad cleaning tape based on a one-sided stamped dimensionally stable HDPE film.

Attributes

Our pad-cleaning tapes combine the actually oppositional properties of safe removal from tint and dirt with avoiding adhesion transfer.

SynTape® TRB19 Optimo is also excellent for machine processing.

Application

Cleaning of pad printheads

Delivery forms

- Core diameter 76 mm ± 3 % (further diameters on request)
- Slotted cores are possible
- Standard length: 40 m and 50 m (further lengths on request)
- Special widths on request

Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

General	Unit of measure	
Adhesiveness / Adhesion to steel	N/cm	1.4
Type/ Ordering information		SynTape® TRB19 Optimo
Standard colours		transparent
Backing (Laminate)		HDPE-film
Backing thickness	mm	0.13 ± 10 %
Adhesive		acrylate

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 01/19

