Product datasheet Isotape® 4560PV3 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



| Isotane® | 4560PV3 |
|----------|---------|
| isotabe | 420UPV3 |

Isotape® 4560PV3 consists of acetate cloth with rubber adhesive.

Delivery forms

- Width: from 2.5 mm in 0.1 mm increments
- Core diameter: 76 mm (3")
- Special widths on request

| Color | | | |
|--------------|--|--|--|
| White, black | | | |
| | | | |
| Glue | | | |
| Rubber | | | |
| | | | |
| Adhesive | | | |
| One-sided | | | |
| | | | |

Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.





Product datasheet Isotape® 4560PV3 Page 2 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



| General | Unit of measure | |
|----------------------------------|-----------------|------------------|
| Type/ Ordering information | | Isotape® 4560PV3 |
| Standard colours | | White, black |
| Backing | | Acetate cloth |
| Backing thickness | mm | 0.190 |
| Adhesive | | Rubber |
| Total thickness | mm | 0.260 |
| Elongation at break | % | 16 |
| Dielectic strength | kV | 2.5 |
| Tensile strength | N/cm | 62.8 |
| Adhesiveness / Adhesion to steel | N/cm | 2.56 |
| Thermal class | | 130 °C (B) |





