Product datasheet Isotape® 51600PV3 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



| Isotape® 51600PV3 | | | |
|---|--|--|--|
| Isotape® 51600PV3 is a woven polyester tape with acrylate adhesive. | | | |
| Delivery forms | | | |
| Width: from 2.5 mm in 0.1 mm increments | | | |
| • Core diameter: 76 mm (3") | | | |
| Special widths on request | | | |
| | | | |
| Color | | | |
| White | | | |
| Glue | | | |
| Acrylate | | | |
| Adhesive | | | |
| One-sided | | | |

Storage

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 12 months.





Product datasheet Isotape® 51600PV3 Page 2 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



| General | Unit of measure | |
|----------------------------------|-----------------|--------------------|
| Type/ Ordering information | | Isotape® 51600 PV3 |
| Standard colours | | White |
| Backing | | Woven polyester |
| Backing thickness | mm | 0.100 |
| Adhesive | | Acrylate |
| Total thickness | mm | 0.160 |
| Dielectric strength | kV | 2.2 |
| Elongation at break | % | 35 |
| Tensile strength | N/cm | 125 |
| Adhesiveness / Adhesion to steel | N/cm | 3.5 |
| Thermal class | | 130 °C (B) |





