Product datasheet Isotape® 52403 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



lent:	no®	524	U3
SOLO	ine	224	บร

Isotape® 52403 consists of paper reinforced glass fiber with acrylate adhesive.

## **Delivery forms**

- Width: from 2.5 mm in 0.1 mm increments
- Core diameter: 76 mm (3")
- Special widths on request

Color	
White	
Glue	
Acrylate	
Adhesive	
One-sided	

## Storage

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 12 months.





Product datasheet Isotape® 52403 Page 2 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		Isotape® 52403
Standard colours		White
Backing		Scrim glass fiber reinforced paper
Backing thickness	mm	0.200
Adhesive		Acrylate
Total thickness	mm	0.255
Dielectric strength	kV	4
Elongation at break	%	8
Tensile strength	N/cm	372
Adhesiveness / Adhesion to steel	N/cm	4.7
Thermal class		155 °C (F)





