Product datasheet SynTape® 1695 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



SynTape® 1695

SynTape 1695 consists of a metalized polyester film as a backing with a thermosetting acrylate adhesive.

Attributes

High resistance to chemicals, solvents and moisture.

Application

As a splice and reflector adhesive tape for the identification of fabric defects by sensors, for repairing and splicing thermal insulation tarpaulins and for horticultural planning.

Delivery forms

• Width: from 2.5 mm, in 0.1 mm increments

Standard lengths: 66 m rolls
Core diameter: 76 mm (3")
Special widths on request

CI		^
u	u	e

Acrylate

Adhesive

one-sided

Storage

6 months at room temperature. Adhesive tapes should always be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.





Product datasheet SynTape® 1695 Page 2 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		1695
Standard colours		silver
Backing		Polyester film metalized
Backing thickness	mm	0.025
Adhesive		Acrylate
Tensile strength	N/cm	30
Total thickness	mm	0.070
Elongation at break	%	100
Adhesiveness / Adhesion to steel	N/cm	4.5



