Product datasheet SynTape® A/ CP.50 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



SynTape® A/ CP.	.50
-----------------	-----

SynTape® A/ CP.50 is a slightly creped paper adhesive tape.

#### **Attributes**

Special feature of the tape is its good initial adhesiveness on various surfaces due to the ductile rubber adhesive.

## **Application**

Final insulation for the production of motors and coil insulation.

## **Delivery forms**

• Width: From 2.5 mm, in 0.1 mm increments

Standard length: 50 m
Core diameter: 76 mm (3")
Special widths on request

GI	ue
----	----

Rubber

#### **Adhesive**

one-sided

# Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.





Product datasheet SynTape® A/ CP.50 Page 2 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Electrolyt. corrosion value		1
Thermal class		105 °C/ A
Dielectic strength	kV	1
Adhesive		Rubber
Total thickness	mm	0.150
Tensile strength	N/cm	45
Elongation at break	%	9
Adhesiveness / Adhesion to steel	N/cm	2.5
Backing thickness	mm	0.110
Backing		slightly creped paper
Standard colours		cream
Type/ Ordering information		A/ CP.50



