Product datasheet Intertape® 4618 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



Intertape® 4618			
Intertape $^{\circ}$ 4618 consists of glass cloth with thermosetting silicone adhesive.			
Standards			
UL-File-Nr.: E20780			
CSA-File: LR94980			
Delivery forms			
Width: from 2.5 mm in 0.1 mm increments			
• Core diameter: 76 mm (3")			
Special widths on request			
Color			
White			
Glue			
Silicone thermosetting			
Adhesive			
One-sided			
Storage			

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 $^{\circ}$ C and 50 - 60 $^{\circ}$ C relative humidity. The storage period should not exceed 12 months.







SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		Intertape® 4618
Standard colours		White
Backing		glass cloth
Backing thickness	mm	0.127
Adhesive		Silicone thermosetting
Total thickness	mm	0.178
Elongation at break	%	3
Insulation resistance	ΜΩ	10^3
Electrolyt. corrosion value		1.0 Direct/A, 1
Flammability class		BU 1
Thermal class		200 °C (N)
Dielectic strength	kV	2.5
Tensile strength	N/cm	324
Adhesiveness / Adhesion to steel	N/cm	4.9





