Product datasheet Isotape® 51350PV3 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



Isotan	®	51	35	۸D۱	/3
ISOLAD	160	71	77	UP	רע

Isotape[®] 51350PV3 is a polyester film tape with acrylate adhesive.

Delivery forms

- Width: from 2.5 mm in 0.1 mm increments
- Core diameter: 76 mm (3")
- Special widths on request

C0	i	_	×
L O	ı	O	r

Yellow, white, black, blue, red, green, transparent.

Glue

Acrylate

Adhesive

One-sided

Storage

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 12 months.







SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		Isotape® 51350PV3
Standard colours		Yellow, white, black, blue, red, green, transparent
Backing		Polyester film
Backing thickness	mm	0.025
Adhesive		Acrylate
Total thickness	mm	0.060
Dielectric strength	kV	5
Elongation at break	%	100
Tensile strength	N/cm	43
Adhesiveness / Adhesion to steel	N/cm	3.9
Thermal class		130 °C (B)





