Product datasheet Isotape® 51579PV3 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



Isotape® 51579PV3
$Isotape^{\$}$ 51579PV3 is an adhesive tape consisting of polyimid film and acrylate adhesive.
Attributes
Isotape® 51579PV3 is suitable especially for high temperature applications (F/155°C).
Application
Generators
• Capacitors
Transformers
Delivery forms
Width: from 2.5 mm in 0.1 mm increments
• Core diameter: 76 mm (3")
Special widths on request
Color
Brown transparent
Glue
Acrylate
Adhesive
One-sided

Storage

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 $^{\circ}$ C and 50 - 60 $^{\circ}$ C relative humidity. The storage period should not exceed 12 months.







SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		Isotape® 51579PV3
Standard colours		Brown-transparent
Backing		Polyimide film
Backing thickness	mm	0.025
Adhesive		Acrylate
Total thickness	mm	0.072
Dielectric strength	kV	6.5
Elongation at break	%	80
Tensile strength	N/cm	55
Adhesiveness / Adhesion to steel	N/cm	3.3
Thermal class	°C	155 (F)







