Product datasheet Isotape® 6215PV3 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



sotape®	6215PV3
---------	---------

Isotape® 6215PV3 is a polyester film tape with silicone adhesive.

Delivery forms

- Width: from 2.5 mm in 0.1 mm increments
- Core diameter: 76 mm (3")
- Special widths on request

Color	
Green translucent	
Glue	
Silicone	
Adhesive	
One-sided	

Storage

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 $^{\circ}$ C and 50 - 60 $^{\circ}$ C relative humidity. The storage period should not exceed 12 months.







SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		Isotape® 6215PV3
Standard colours		Green translucent
Backing		Polyester film
Backing thickness	mm	0.050
Adhesive		Silicone
Total thickness	mm	0.089
Dielectric strength	kV	6
Elongation at break	%	110
Tensile strength	N/cm	78
Adhesiveness / Adhesion to steel	N/cm	3.5
Thermal class		130 °C (B)





