

---

## SynTape® B 107/ P.31

SynTape® B 107/ P.31 is a polyester adhesive tape with good adhesiveness due to the thermosetting rubber adhesive.

---

### Attributes

SynTape® B 107 / P.31 is available as a transparent, yellow or beige universal tape (blue, black and creme on request). It has good resistance to impregnants.

---

### Application

As core and interlayer insulation, final insulation, taping and insulation of transformers, coils and wires, UL approved.

---

### Delivery forms

- Width: From 2.5 mm, in 0.1 mm increments
- Standard length: 66 m
- Core diameter: 76 mm (3")
- Special widths on request

---

### Glue

Rubber

---

### Adhesive

one-sided

---

### Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

General	Unit of measure	
Type/ Ordering information		B 107 / P.31
Standard colours		transparent, yellow, light yellow (blue, black, cream on request)
Backing		Polyester film
Backing thickness	mm	0.023
Adhesive		Rubber
Electrolyt. corrosion value		1
Thermal class	°C	130 (B)
Dielectric strength	kV	4.5
Adhesiveness / Adhesion to steel	N/cm	5
Elongation at break	%	80
Tensile strength	N/cm	40
Total thickness	mm	0.060