

---

## SynTape® H/ 560

SynTape® H / 560 is a polyimide adhesive tape with silicone adhesive for the highest electrical and thermal demands.

---

### Attributes

Constant, good adhesiveness over a large temperature range, high dielectric strength and smooth removal from the roll. Flame retardant according to UL 510.

---

### Application

Masking of printed circuit board contacts when soldering with subsequent residue-free removal.

---

### Delivery forms

- Width: From 2.5 mm, in 0.1 mm increments
- Standard lengths: 33 m
- Core diameter: 76 mm (3")
- Special widths on request

---

### Glue

Silicone

---

### Adhesive

one-sided

---

### Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

| General                          | Unit of measure |           |
|----------------------------------|-----------------|-----------|
| Type/ Ordering information       |                 | H/ 560    |
| Standard colours                 |                 | brown     |
| Backing                          |                 | Polyimide |
| Backing thickness                | mm              | 0.025     |
| Adhesive                         |                 | Silicone  |
| Thermal class                    |                 | 180 °C/ H |
| Flame retardant                  |                 | UL510     |
| Electrolyt. corrosion value      |                 | 1         |
| Dielectric strength              | kV              | 6.0       |
| Elongation at break              | %               | 35        |
| Tensile strength                 | N/cm            | 40        |
| Total thickness                  | mm              | 0.060     |
| Adhesiveness / Adhesion to steel | N/cm            | 2.3       |