Product datasheet SynTape® F/ PX.50 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



# SynTape® F/ PX.50

SynTape® F/ PX.50 is a Nomex® polyester adhesive tape with high adhesiveness due to the rubber adhesive.

#### **Attributes**

An enhanced dielectric strength is achieved via laminating the tape with a polyester film. UL approved.

## **Application**

For electrical insulation at high thermal loads and as final insulation.

#### **Delivery forms**

• Width: From 2.5 mm, in 0.1 mm increments

Standard length: 50 m
Core diameter: 76 mm (3")
Special widths on request

	 _

Rubber

### **Adhesive**

one-sided

#### **Storage**

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20  $^{\circ}$ C and 50 - 60  $^{\circ}$ C relative humidity. The storage period should not exceed 6 months.







SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		F/ PX.50
Standard colours		cream
Backing		Nomex® / Polyester
Backing thickness	mm	0.090
Adhesive		Rubber
Thermal class		155 ° C/ F
Total thickness	mm	0.135
Tensile strength	N/cm	65
Elongation at break	%	10
Adhesiveness / Adhesion to steel	N/cm	5.5
Dielectic strength	kV	7
Electrolyt. corrosion value		1





