
SynTape® A 560/ CA.100

SynTape® A 560/ CA.100 is an acetate rayon adhesive tape with rubber adhesive.

Attributes

Easy-to-form, varnish and resin resistant adhesive tape, displays excellent adhesion even to wild windings, high initial adhesiveness.

Application

Final insulation of coils, as stress relief for supply lines, and masking the winding start and end as well as cantilever coils.

Standards

RoHS compliant according to 2011/65/EU.

Delivery forms

- Width: From 2.5 mm, in 0.1 mm increments
- Standard length: 50 m
- Core diameter: 76 mm (3")
- Special widths on request

Glue

rubber

Adhesive

one-sided

Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

General	Unit of measure	
Type/ Ordering information		A 560/ CA.100
Standard colours		white or black
Backing		Acetate fabric
Backing thickness	mm	0.160
Adhesive		Rubber
Thermal class		105 °C/ A
Total thickness	mm	0.210
Tensile strength	N/cm	55
Elongation at break	%	10
Adhesiveness / Adhesion to steel	N/cm	1.8
Dielectric strength	kV	1.5
Electrolyt. corrosion value		1

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 06/19

