Product datasheet Isotape® 52204 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



Isotape® 52204
Isotape® 52204 is a non-woven polyester double-sided tape with acrylate adhesive.
Delivery forms

Core diameter: 76 mm (3")Special widths on request

• Width: from 2.5 mm in 0.1 mm increments

White	
Glue	
Acrylate	
Adhesive	
Double-sided	

Storage

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 12 months.

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 07/20









Product datasheet Isotape® 52204 Page 2

SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		Isotape® 52204
Standard colours		White
Backing		Non-woven Polyester
Adhesive		Acrylate
Total thickness	mm	0.100
Adhesiveness / Adhesion to steel	N/cm	10





Isotape® is a registered trademark of

