Product datasheet SynTape® B/ P.231 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



SynTape® B/ P	.2	31
---------------	----	----

SynTape[®] B/ P.231 is a double-sided adhesive polyester tape.

Attributes

Double-sided adhesive polyester tape with good flexibility.

Application

Ideal for electrical insulation on busbars or for the masking of pressboards and laminates in the final binding band.

Delivery forms

• Width: from 2.5 mm in steps of 0.1 mm

Standard lengths: 66 m rollsCore diameter: 76 mm (3")

• Special widths on request

Glue

Rubber

Adhesive

double-sided

Storage

Updated 01/17

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.







SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Thermal class		130 °C/ B
Dielectic strength	kV	4.5
Adhesiveness / Adhesion to steel	N/cm	5
Elongation at break	%	80
Tensile strength	N/cm	40
Total thickness	mm	0.090
Adhesive		Rubber
Backing thickness	mm	0.023
Backing		Polyester film
Standard colours		yellow
Type/ Ordering information		B/P.231





