
SynTape® F/ PVX.30

SynTape® F/ PVX.30 is a glass-fibre-reinforced polyester tape of thermal class F (155 °C) with acrylic adhesive.

Attributes

SynTape® F/ PVX.30 has a very high resistance to tears and good resistance to impregnants.

Application

It can be used as a final bandage, for sticking down the start and end of windings, sticking supply lines and for strain relief (mechanical reinforcement).

Delivery forms

- Width: from 2.5 mm in steps of 0.1 mm
- Standard length: 66 m
- Core diameter: 76 mm (3")
- Special widths on request

Glue

acrylate

Adhesive

one-sided

Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

General	Unit of measure	
Electrolyt. corrosion value		1
UL FILE NO.		E178 430
Thermal class		155 ° C/ F
Dielectric strength	kV	5
Adhesiveness / Adhesion to steel	N/cm	6.0
Elongation at break	%	4
Tensile strength	N/cm	380
Total thickness	mm	0.170
Adhesive		Acrylat
Backing thickness	mm	0.110
Backing		Glass fibre reinforced polyester
Standard colours		translucent
Type/ Ordering information		F/ PVX.30