
SynTape® A16-320

The S-4210 NH adhesive (SynFlex item A16-320) is a solvent free modified acrylate adhesive.

Attributes

High immediate adhesiveness to most materials, even to materials with low surface tension, and displays high peel off strength, good UV humidity and ageing resistance.

Application

The acrylate adhesive can be used for numerous applications and is applied in various industrial sectors, e.g. in the automotive industry.

Delivery forms

- Width: From 5.0 mm, in 0.1 mm increments
- Standard length: 100 m
- Core diameter: 76 mm (3")
- Special widths on request

Glue

Acrylate

Adhesive

double-sided

Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

General	Unit of measure	
Type/ Ordering information		S- 4210 NH (SynFlex ident. A16-320)
Backing		Non-woven, 12 g/ m ²
Adhesive		Acrylate
Adhesive weight		90 g/ m ²
Interliner		Release paper, yellow, 90 g/ m ²
Adhesiveness / Adhesion to steel	N/25 mm	16
Thermal resistance		-40 °C up to +100 °C
Total thickness	mm	0.100

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 01/17

