

---

## SynTape® B/ P.355

SynTape® B/ P.355 is a polyester adhesive tape with acrylic adhesive.

---

### Attributes

The B/ P.355 polyester adhesive tape is characterised by good mechanical resilience and good green strength.

---

### Application

As a corer and insulation layer, final insulation, taping and insulation of coils and wires. The tape is characterised by its broad range of uses.

---

### Delivery forms

- Width: from 2.5 mm in steps of 0.1 mm
- Standard length: 66 m
- Core diameter: 76 mm (3")
- Special widths on request

---

### Glue

acrylate

---

### Adhesive

one-sided

---

### Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

General	Unit of measure	
Electrolyt. corrosion value		1
Thermal class		130 ° C/ B
Dielectric strength	kV	7
Adhesiveness / Adhesion to steel	N/cm	6.0
Elongation at break	%	100
Tensile strength	N/cm	70
Total thickness	mm	0.087
Adhesive		Acrylate
Backing thickness	mm	0.050
Backing		Polyester film
Standard colours		Yellow and transparent
Type/ Ordering information		B/ P.355

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 01/17

