SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



SynTape® TRB16 Eco

SynTape® TRB16 Eco is a transparent pad-cleaning tape based on one-sided stamped polypropylene-film with excellent flatness.

Attributes

Our pad-cleaning tapes combine the actually opositional properties of safe removal from tint and dirt with avoiding adhesion transfer.

SynTape® TRB16 Eco is also excellent for machine processing.

Application


Cleaning of pad printheads

Delivery forms

- Core diameter 76 mm ± 3 % (further diameters on request)
- Slotted cores are possible
- Standard length: 40 m and 50 m (further lengths on request)
- Special widths on request

Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.











SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		SynTape® TRB16 Eco
Standard colours		transparent
Backing (Laminate)		polypropylene
Backing thickness	mm	0.090 ± 10 %
Adhesiveness / Adhesion to steel	N/cm	1.2
Adhesive		acrylate





