Product datasheet Isotape® 4239 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



Isotape® 4239

Isotape® 4239 is a fibreglass reinforced polyester tape with a pressure sensitive acrylate adhesive.

Delivery forms

• Width: from 2.5 mm in 0.1 mm increments

Core diameter: 76 mm (3")Special widths on request

_		
r	\sim	14

Translucent

Glue

Pressure sensitive acrylate

Adhesive

One-sided

Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet. Updated 05/24

Isotape® is a registered trademark of SynFlex.





Product datasheet Isotape® 4239 Page 2

SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		Isotape® 4239
Standard colours		Translucent
Backing		Glass fiber reinforced polyester
Adhesive		Pressure sensitive acrylate
Total thickness	mm	0.180
Elongation at break	%	10
Thermal class		155 °C (F)
Dielectic strength	kV	6
Adhesiveness / Adhesion to steel	N/cm	4.68
Tensile strength	N/cm	392
Backing thickness	mm	0.130

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet. Updated 05/24

 $\label{local_solution} Isotape \ensuremath{\$}\ is a registered trademark of SynFlex.$



