

---

## Syntape® B/ PR.30

Syntape® B/ PR.30 is a glass fibre reinforced polyester tape with rubber adhesive.

---

### Attributes

Besides a high resistance to tears, Syntape® B/ PR.30 is characterised by its high initial adhesiveness.

---

### Application

As stress relief and mechanical reinforcement, as well as for masking the winding start and end.

---

### Standards

RoHS compliant according to 2011/65/EU.

---

### Delivery forms

- Width: From 2.5 mm, in 0.1 mm increments
- Standard length: 50 m
- Core diameter: 76 mm (3")
- Special widths on request

---

### Glue

Rubber

---

### Adhesive

one-sided

---

### Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

General	Unit of measure	
Type/ Ordering information		B/ PR.30
Standard colours		translucent
Backing		Polyester glass filament reinforced
Backing thickness	mm	0.100
Adhesive		Rubber
Total thickness	mm	0.175
Tensile strength	N/cm	550
Elongation at break	%	5
Adhesiveness / Adhesion to steel	N/cm	4.0
Dielectric strength	kV	5
Thermal class		130 °C/ B
UL FILE NO.		E 178430
Electrolyt. corrosion value		1

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 01/17

Syntape® is a registered trademark of SynFlex.

