
SynTape® F/ H.50AC

SynTape® F/ H.50AC is a Kapton® adhesive tape with acrylate adhesive for the highest electrical and chemical demands, and thermal demands in particular.

Attributes

Very high dielectric strength and high mechanical strength even at elevated temperatures.

Application

Insulation tape for the highest demands.

Standards

RoHS compliant according to 2011/65/EU.

Delivery forms

- Width: From 2.5 mm, in 0.1 mm increments
- Standard length: 66 m
- Core diameter: 76 mm (3")
- Special widths on request

Glue

Acrylate

Adhesive

one-sided

Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

General	Unit of measure	
Type/ Ordering information		F/ H.50AC
Standard colours		brown
Backing		Kapton®
Backing thickness	mm	0.050
Adhesive		Acrylate
Thermal class		155 °C/ F
Total thickness	mm	0.090
Tensile strength	N/cm	75
Elongation at break	%	35
Adhesiveness / Adhesion to steel	N/cm	3.8
Dielectric strength	kV	10
Electrolyt. corrosion value		1

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 01/17

Nomex®, Kapton®, KAPTON® sind eingetragene Marken von E.I. Du Pont de Nemours and Company

