
SHBond® WD210 Glide

- Enamelled round copper wire, thermoresistant, selfbonding and self lubricating
- Insulated with THEIC mod. polyesterimide
- plus polyamide-imide overcoat plus bonding layer
- Class 200

Attributes

SHBond® WD210 Glide is a highly thermoresistant self-bonding enamelled copper wire of heat performance class N. With this wire the excellent resistance and insulation properties of SHTherm® 210 - Dualcoat are combined with the special application possibilities of an additional bonding layer which is based on mod. aromat. polyamide and which enables the production of heat bonded wire windings. Using this type of thermo-setting wire the heat bonding process is economic, as it can be executed within seconds and can support automatic processing. It is not harmful to the environment. Heat bonded windings show excellent thermal and mechanical stability and high resistance to climatic demands and many chemical agents. Sophisticated process technology and process setting ensure easy mouldability, good elongation and excellent insulation properties.

The final layer of varnish serves the purpose of providing a superior gliding surface, giving the wire excellent windability features at higher speeds, and enabling a higher filling factor plus reduced soiling of the winding machines. The reduced coefficient of friction helps to avoid damage to the wire during winding and thus maintains the insulation properties of the wire.

Application

Drives for household appliances, pole windings, wire wound coils, power tools

Standards

IEC / DIN EN 60317-38

NEMA MW 102-C

Delivery forms

Grade 1: on request

Grade 2: on request

Typical properties of enamelled round copper wire 0.500 mm, with insulation film grade 1B

| Mechanical | Unit of measure | Set value | Actual value (typ.) |
|--|-----------------|---------------------------|-----------------------------|
| Overall diameter | mm | min. 0.541 - max. 0.568 | as set value |
| Bare wire diameter | mm | 0.495-0.505 | as set value |
| Adhesion (no cracks in film after winding) | | mandrel diameter 0.500 mm | 1 x d / 10 % pre-elongation |
| Scrape resistance | N | ≥ 3.950 | ≥ 7.500 |
| Pencil hardness | | H | 3H - 5H |
| Elongation at break | % | ≥ 28 | ≥ 38 |
| Coefficient of friction | μ | / | ≤ 0.110 |

| Thermal | Unit of measure | Set value | Actual value (typ.) |
|--|-----------------|---------------------------|-----------------------------|
| Temperature index TI | °C | 200 | 210 |
| Cut through temperature (pre-heated block) | °C | 320 | ≥ 360 |
| Dielectric loss factor (bending point) | (°C) (tan δ) | / | ≥ 140/185/240 |
| Heat shock at 220 °C (no cracks in varnish coat after winding) | | mandrel diameter 1.120 mm | 1 x d / 10 % pre-elongation |
| Bonding temperature | °C | 200 +/-2 | ≥ 210 |

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 06/18



| Electrical | Unit of measure | Set value | Actual value (typ.) |
|--------------------------------------|-----------------|---------------|---------------------|
| Dielectrical strength at RT | kV | ≥ 2.4 (twist) | ≥ 3 (cylinder) |
| High voltage discontinuities 750V | | ≤ 10 on 30 m | ≤ 7 on 100 m |
| Electrical conductivity | MS/m | 58 - 59 | ≥ 58.5 |

| Chemical | Set value | Actual value (typ.) |
|---|-------------------------|---------------------|
| Pencil hardness (storage in standard solvent ½ h / 60 °C) | test methods unsuitable | / |
| Pencil hardness (storage in alcohol ½ h / 60 °C) | / | |
| Resistance to commercial impregnants^(1) | / | not applicable |
| Resistance to commercial refrigerants^(1) | / | limited |
| Resistance to commercial dry transformer oils^(1) | / | not recommended |
| Resistance to commercial hydraulic oils^(1) | / | no |

(1) Due to the variety of individual applications we cannot make any generally binding commitments regarding the compatibility. We recommend testing compatibility with the materials being used.