

---

## Isotape® 4637PV3

Isotape® 4637PV3 is a glass cloth tape with acrylate adhesive.

---

### Standards

UL-File-No.: E315249

---

### Delivery forms

- Width: from 2.5 mm in 0.1 mm increments
- Core diameter: 76 mm (3")
- Special widths on request

---

### Color

White

---

### Glue

Acrylate

---

### Adhesive

One-sided

---

### Storage

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 12 months.

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 05/24



| General                          | Unit of measure |                  |
|----------------------------------|-----------------|------------------|
| Type/ Ordering information       |                 | Isotape® 4637PV3 |
| Standard colours                 |                 | White            |
| Backing                          |                 | Glass cloth      |
| Backing thickness                | mm              | 0.145            |
| Adhesive                         |                 | Acrylate         |
| Total thickness                  | mm              | 0.180            |
| Elongation at break              | %               | 7                |
| Dielectric strength              | kV              | 2.5              |
| Tensile strength                 | N/cm            | 235              |
| Adhesiveness / Adhesion to steel | N/cm            | 5.3              |
| Thermal class                    |                 | 155 °C (F)       |

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 05/24

