SynFlex Elektro GmbH
Auf den Kreuzen 24
D-32825 Blomberg Germany
Telefon +49-5235-968-0
E-Mail info@synflex.de

SynTape® B/ P.231

SynTape® B/ P.231 is a double-sided adhesive polyester tape.

Attributes

Double-sided adhesive polyester tape with good flexibility.

Application

Ideal for electrical insulation on busbars or for the masking of pressboards and laminates in the final binding band.

Delivery forms

- Width: from 2.5 mm in steps of 0.1 mm
- Standard lengths: 66 m rolls
- Core diameter: 76 mm (3")
- Special widths on request

Glue

Rubber

Adhesive

double-sided

Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.
Updated 01/17

SynFlex Elektro GmbH
Auf den Kreuzen 24
D-32825 Blomberg Germany
Telefon +49-5235-968-0
E-Mail info@synflex.de

General	Unit of measure	
Thermal class		130 °C/ B
Dielectic strength	kV	4.5
Adhesiveness / Adhesion to steel	N/cm	5
Elongation at break	%	80
Tensile strength	N/cm	40
Total thickness	mm	0.090
Adhesive		Rubber
Backing thickness	mm	0.023
Backing		Polyester film
Standard colours		yellow
Type/ Ordering information		B/P.231

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.
Updated 01/17