
Isotape® 4560PV3

Isotape® 4560PV3 consists of acetate cloth with rubber adhesive.

Delivery forms

- Width: from 2.5 mm in 0.1 mm increments
- Core diameter: 76 mm (3")
- Special widths on request

Color

White, black

Glue

Rubber

Adhesive

One-sided

Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

General	Unit of measure	
Type/ Ordering information		Isotape® 4560PV3
Standard colours		White, black
Backing		Acetate cloth
Backing thickness	mm	0.190
Adhesive		Rubber
Total thickness	mm	0.260
Elongation at break	%	16
Dielectric strength	kV	2.5
Tensile strength	N/cm	62.8
Adhesiveness / Adhesion to steel	N/cm	2.56
Thermal class		130 °C (B)

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 07/20

